


# 460 S&W MAG.

## XRG-D 260 GRS SB460C



This solid copper hollow-point bullet construction results in near 100% weight retention regardless of the barriers encountered. Light-for-caliber bullet weights produce low perceived recoil, high velocity, and reliable expansion from today's compact personal defense handguns. The impressive, real-world performance of XRG Defense has been proven by many European Law Enforcement units.



### PROPERTIES

BULLET	TYPE		XRG-D
	WEIGHT	grs	260
	DIAMETER	in	0.452
	SECTIONAL DENSITY	lb/in <sup>2</sup>	0.182
	MATERIAL OF JACKET		-
BALLISTIC COEFFICIENT		G1	0.230
PRIMER	TYPE		N/A
	STYLE		N/A
CARTRIDGE	LENGTH	in	2.288
CASINGS			Factory Brass
POWER FACTOR ESTIMATED		kgr-fps	500.0
+P AMMUNITION			No
TEST BARREL LENGTH		in	8¼
SUGGESTED USE			N/A
FEATURES			N/A
PACKAGING			
BOXES PER CASE			12
WEIGHT PER CASE		lb	17.6

### BALLISTICS

DISTANCE	y	MUZZLE	25	50	100
VELOCITY	fps	1,923	1,841	1,762	1,612
ENERGY	ft-lb	2,134	1,957	1,792	1,499
DISTANCE	y	12.5	25	50	100
POINTS OF IMPACT	in	-0.2	0.0	-0.2	-2.7

