

6,8 mm REM. SPC

FMJ ^{110 GRS} SB68C



Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.



PROPERTIES

BULLET	TYPE	FMJ
	WEIGHT	grs 110
	DIAMETER	in 0.277
	SECTIONAL DENSITY	lb/in ² 0.205
	MATERIAL OF JACKET	CuZn 10
BALLISTIC COEFFICIENT	G1	0.307
	G7	0.155
CARTRIDGE	LENGTH	in 2.244
POWER FACTOR ESTIMATED	kgr-fps	281.2
TEST BARREL LENGTH	in	16¼
SUGGESTED USE		Range, Match/Competition
FEATURES		Reliable Functioning, Non-expanding, No Barrel Leading

PACKAGING

BOXES PER CASE	50
WEIGHT PER CASE	lb 39.7

BALLISTICS

DISTANCE	y	MUZZLE	100	200	300	400
VELOCITY	fps	2,556	2,275	2,013	1,767	1,536
ENERGY	ft-lb	1,595	1,264	989	763	576
DISTANCE	y	50	100	200	300	400
POINTS OF IMPACT	in	-0.3	0.0	-4.8	-18.1	-42.7

