



# 7,62 × 51

## FMJ SUBSONIC

200 GRS  
SB762SUBB



### PROPERTIES

|                               |                    |                             |
|-------------------------------|--------------------|-----------------------------|
| <b>BULLET</b>                 | TYPE               | FMJ SUBSONIC                |
|                               | WEIGHT             | grs 200                     |
|                               | DIAMETER           | in 0.308                    |
|                               | SECTIONAL DENSITY  | lb/in <sup>2</sup> 0.301    |
|                               | MATERIAL OF JACKET | CuZn 10                     |
| <b>BALLISTIC COEFFICIENT</b>  | G1                 | 0.558                       |
|                               | G7                 | 0.242                       |
| <b>CARTRIDGE</b>              | LENGTH             | in 2.799                    |
| <b>POWER FACTOR ESTIMATED</b> | kgr-fps            | 482.2                       |
| <b>TEST BARREL LENGTH</b>     | in                 | 23½                         |
| <b>SUGGESTED USE</b>          |                    | Range,<br>Match/Competition |
| <b>FEATURES</b>               |                    | N/A                         |

### PACKAGING

|                        |       |
|------------------------|-------|
| <b>BOXES PER CASE</b>  | 25    |
| <b>WEIGHT PER CASE</b> | lb 32 |

### BALLISTICS

|                         |       |        |     |       |        |        |
|-------------------------|-------|--------|-----|-------|--------|--------|
| <b>DISTANCE</b>         | y     | MUZZLE | 100 | 200   | 300    | 400    |
| <b>VELOCITY</b>         | fps   | 1,030  | 991 | 957   | 925    | 896    |
| <b>ENERGY</b>           | ft-lb | 471    | 436 | 406   | 380    | 356    |
| <b>DISTANCE</b>         | y     | 50     | 100 | 200   | 300    | 400    |
| <b>POINTS OF IMPACT</b> | in    | 3.3    | 0.0 | -33.4 | -104.8 | -216.8 |

