

10 mm AUTO

JHP V312272 180 GRS



Jacketed Hollow Point bullet. Standard 2 piece bullet construction designed for reliable feeding and function in a wide variety of firearms. An excellent defensive projectile.



PROPERTIES

| | | | |
|-------------------------------|--------------------|--------------------|-------|
| BULLET | TYPE | JHP | |
| | WEIGHT | grs | 180 |
| | | g | 11.70 |
| | SECTIONAL DENSITY | lb/in ² | 0.161 |
| | MATERIAL OF JACKET | CuZn 10 | |
| | NUMBER | N/A | |
| BALLISTIC COEFFICIENT | | G1 | 0.246 |
| CARTRIDGE | WEIGHT | g | 17.3 |
| | LENGTH | mm | 32.00 |
| CASINGS | | Factory Brass | |
| POWER FACTOR ESTIMATED | | kgr-fps | 209.7 |
| +P AMMUNITION | | No | |
| TEST BARREL LENGTH | | mm | 150 |
| SUGGESTED USE | | N/A | |
| FEATURES | | N/A | |
| PACKAGING | | | |
| BOXES PER CASE | | 20 | |
| WEIGHT PER CASE | | kg | 18.6 |
| | | lb | N/A |

BALLISTICS

| | | | | | |
|-------------------------|-----|--------|-----|------|-------|
| DISTANCE | m | MUZZLE | 25 | 50 | 100 |
| VELOCITY | m/s | 355 | 343 | 332 | 314 |
| ENERGY | J | 737 | 687 | 643 | 575 |
| DISTANCE | m | 12.5 | 25 | 50 | 100 |
| POINTS OF IMPACT | cm | -0.1 | 0.0 | -3.7 | -28.2 |

