

7,62 × 39 FMJ

V340832
124 GRS



Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.



PROPERTIES

| | | | |
|------------------------------|--------------------|--|-------|
| BULLET | TYPE | FMJ | |
| WEIGHT | grs | 124 | |
| | g | 8.00 | |
| SECTIONAL DENSITY | lb/in ² | 0.183 | |
| MATERIAL OF JACKET | | CuZn 10 | |
| NUMBER | | 2907 | |
| BALLISTIC COEFFICIENT | G1 | 0.286 | |
| | G7 | 0.143 | |
| MRD | m | 147 | |
| CARTRIDGE | WEIGHT | g | 17.5 |
| | LENGTH | mm | 56.00 |
| CASINGS | | Factory Brass | |
| POWER FACTOR ESTIMATED | kg-fps | 300.2 | |
| +P AMMUNITION | | No | |
| TEST BARREL LENGTH | mm | 520 | |
| SUGGESTED USE | | Range, Match/Competition | |
| FEATURES | | Reliable Functioning, Non-expanding, No Barrel Leading | |
| PACKAGING | | | |
| BOXES PER CASE | | 30 | |
| WEIGHT PER CASE | kg | 11.4 | |
| | lb | 25.1 | |

BALLISTICS

| | | | | | | |
|----------------------|-----|--------|-------|-------|-------|--------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 738 | 640 | 550 | 466 | 389 |
| ENERGY | J | 2,179 | 1,640 | 1,211 | 870 | 605 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | 0.1 | 0.0 | -19.1 | -71.0 | -168.5 |
| POINTS OF IMPACT MRD | cm | 2.0 | 3.7 | -11.6 | -59.8 | -153.5 |

