

30-06 SPRING. FMJ V331792 180 GRS



Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.



PROPERTIES

| | | | |
|-------------------------------|--------------------|--------------------|--|
| BULLET | TYPE | | FMJ |
| | WEIGHT | grs | 180 |
| | | g | 11.70 |
| | SECTIONAL DENSITY | lb/in ² | 0.271 |
| | MATERIAL OF JACKET | | CuZn 10 |
| | NUMBER | | 2957 |
| BALLISTIC COEFFICIENT | | G1 | 0.498 |
| | | G7 | 0.250 |
| MRD | | m | 169 |
| CARTRIDGE | WEIGHT | g | 27.2 |
| | LENGTH | mm | 82.50 |
| CASINGS | | | N/A |
| POWER FACTOR ESTIMATED | | kg-fps | 481.3 |
| +P AMMUNITION | | | No |
| TEST BARREL LENGTH | | mm | 600 |
| SUGGESTED USE | | | Range, Match/Competition |
| FEATURES | | | Reliable Functioning, Non-expanding, No Barrel Leading |
| PACKAGING | | | |
| BOXES PER CASE | | | 20 |
| WEIGHT PER CASE | | kg | 12.2 |
| | | lb | 27 |

BALLISTICS

| | | | | | | |
|-----------------------------|-----|--------|-------|-------|-------|--------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 815 | 755 | 697 | 642 | 590 |
| ENERGY | J | 3,886 | 3,333 | 2,843 | 2,412 | 2,035 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | -0.5 | 0.0 | -12.3 | -44.7 | -101.1 |
| POINTS OF IMPACT MRD | cm | 1.4 | 3.8 | -4.7 | -33.3 | -85.9 |

