

30 CARBINE FMJ

V332652
110 GRS



Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.



PROPERTIES

| | | | |
|-------------------------------|--------------------|--------------------|--|
| BULLET | TYPE | | FMJ |
| | WEIGHT | grs | 110 |
| | | g | 7.10 |
| | SECTIONAL DENSITY | lb/in ² | 0.166 |
| | MATERIAL OF JACKET | | CuZn 10 |
| | NUMBER | | 2960 |
| BALLISTIC COEFFICIENT | | G1 | 0.154 |
| | | G7 | 0.079 |
| MRD | | m | 115 |
| CARTRIDGE | WEIGHT | g | 12.8 |
| | LENGTH | mm | 42.50 |
| CASINGS | | | N/A |
| POWER FACTOR ESTIMATED | | kg-fps | 222.6 |
| +P AMMUNITION | | | No |
| TEST BARREL LENGTH | | mm | 600 |
| SUGGESTED USE | | | Range, Match/Competition |
| FEATURES | | | Reliable Functioning, Non-expanding, No Barrel Leading |
| PACKAGING | | | |
| BOXES PER CASE | | | 20 |
| WEIGHT PER CASE | | kg | 13.9 |
| | | lb | 30.7 |

BALLISTICS

| | | | | | | |
|-----------------------------|-----|--------|-----|-------|--------|--------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 617 | 461 | 331 | 288 | 259 |
| ENERGY | J | 1,351 | 756 | 389 | 294 | 237 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | 1.8 | 0.0 | -43.1 | -172.7 | -420.7 |
| POINTS OF IMPACT MRD | cm | 2.9 | 2.3 | -38.5 | -165.8 | -411.6 |

