

7 × 64 FMJ

V331162
140 GRS



Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.



PROPERTIES

| | | |
|-------------------------------|--------------------|--------------------------|
| BULLET | TYPE | FMJ |
| | WEIGHT | grs 140 |
| | | g 9.10 |
| | SECTIONAL DENSITY | lb/in ² 0.248 |
| | MATERIAL OF JACKET | CuZn 10 |
| | NUMBER | 2955 |
| BALLISTIC COEFFICIENT | G1 | 0.429 |
| | G7 | 0.214 |
| MRD | m | 173 |
| CARTRIDGE | WEIGHT | g 23.4 |
| | LENGTH | mm 84.00 |
| CASINGS | | N/A |
| POWER FACTOR ESTIMATED | kgf-fps | 388.1 |
| +P AMMUNITION | | No |
| TEST BARREL LENGTH | mm | 600 |
| SUGGESTED USE | | N/A |
| FEATURES | | N/A |
| PACKAGING | | |
| BOXES PER CASE | | 20 |
| WEIGHT PER CASE | kg | 11 |
| | lb | 24.5 |

BALLISTICS

| | | | | | | |
|-----------------------------|-----|--------|-------|-------|-------|-------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 845 | 774 | 705 | 641 | 580 |
| ENERGY | J | 3,249 | 2,722 | 2,264 | 1,870 | 1,531 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | -0.6 | 0.0 | -11.4 | -42.7 | -97.8 |
| POINTS OF IMPACT MRD | cm | 1.3 | 3.8 | -3.9 | -31.3 | -82.7 |

