

# 303 BRITISH

## SP V331332 180 GRS



Semi-jacketed Soft Point bullet. A lead core with a precisely engineered jacket results from its controlled expansion and high weight retention.



### PROPERTIES

|                               |                    |  |
|-------------------------------|--------------------|--|
| <b>BULLET</b>                 | TYPE               | SP   |
|                               | WEIGHT             | grs 180  |
|                               |                    | g 11.70  |
|                               | SECTIONAL DENSITY  | lb/in <sup>2</sup> 0.266   |
|                               | MATERIAL OF JACKET | CuZn 10  |
|                               | NUMBER             | 2940   |
| <b>BALLISTIC COEFFICIENT</b>  | G1                 | 0.305  |
|                               | G7                 | 0.153  |
| <b>MRD</b>                    | m                  | 146  |
| <b>CARTRIDGE</b>              | WEIGHT             | g 26.6   |
|                               | LENGTH             | mm 74.50   |
| <b>CASINGS</b>                |                    | Factory Brass  |
| <b>POWER FACTOR ESTIMATED</b> | kg·fps             | 428.8  |
| <b>+P AMMUNITION</b>          |                    | No   |
| <b>TEST BARREL LENGTH</b>     | mm                 | 600  |
| <b>SUGGESTED USE</b>          |                    | Hunting  |
| <b>FEATURES</b>               |                    | Reliable<br>Functioning, Rapid-<br>Controlled<br>Expansion, Accurate |
| <b>PACKAGING</b>              |                    |  |
| <b>BOXES PER CASE</b>         |                    | 20   |
| <b>WEIGHT PER CASE</b>        | kg                 | 11.8   |
|                               | lb                 | 25.8   |

### BALLISTICS

|                             |     |        |       |       |       |        |
|-----------------------------|-----|--------|-------|-------|-------|--------|
| <b>DISTANCE</b>             | m   | MUZZLE | 100   | 200   | 300   | 400    |
| <b>VELOCITY</b>             | m/s | 726    | 635   | 551   | 473   | 400    |
| <b>ENERGY</b>               | J   | 3,083  | 2,361 | 1,778 | 1,307 | 934    |
| <b>DISTANCE</b>             | m   | 50     | 100   | 200   | 300   | 400    |
| <b>POINTS OF IMPACT</b>     | cm  | 0.2    | 0.0   | -19.5 | -71.5 | -168.0 |
| <b>POINTS OF IMPACT MRD</b> | cm  | 2.0    | 3.7   | -12.0 | -60.4 | -153.1 |

