

# 7 × 65 R

## SPCE V332032 173 GRS



Semi-jacketed Soft Point Cutting Edge bullet. The cutting edge locks the jacket and lead core together, while also producing a clean entrance wound and distinct, easy to follow blood trails. Appropriate for light to medium game.



### PROPERTIES

|                               |                    |                               |       |
|-------------------------------|--------------------|-------------------------------|-------|
| <b>BULLET</b>                 | TYPE               | SPCE                          |       |
|                               | WEIGHT             | grs                           | 173   |
|                               |                    | g                             | 11.20 |
|                               | SECTIONAL DENSITY  | lb/in <sup>2</sup>            | 0.306 |
|                               | MATERIAL OF JACKET | CuZn 10                       |       |
|                               | NUMBER             | 2932                          |       |
| <b>BALLISTIC COEFFICIENT</b>  |                    | G1                            | 0.376 |
|                               |                    | G7                            | 0.189 |
| <b>MRD</b>                    |                    | m                             | 162   |
| <b>CARTRIDGE</b>              | WEIGHT             | g                             | 25.4  |
|                               | LENGTH             | mm                            | 82.50 |
| <b>CASINGS</b>                |                    | Factory Brass                 |       |
| <b>POWER FACTOR ESTIMATED</b> |                    | kg·fps                        | 451.2 |
| <b>+P AMMUNITION</b>          |                    | No                            |       |
| <b>TEST BARREL LENGTH</b>     |                    | mm                            | 680   |
| <b>SUGGESTED USE</b>          |                    | Hunting                       |       |
| <b>FEATURES</b>               |                    | Reliable                      |       |
|                               |                    | Functioning, Rapid-Controlled |       |
|                               |                    | Expansion, Accurate           |       |
| <b>PACKAGING</b>              |                    |                               |       |
| <b>BOXES PER CASE</b>         |                    | 20                            |       |
| <b>WEIGHT PER CASE</b>        |                    | kg                            | 12    |
|                               |                    | lb                            | 26.5  |

### BALLISTICS

|                             |     |        |       |       |       |        |
|-----------------------------|-----|--------|-------|-------|-------|--------|
| <b>DISTANCE</b>             | m   | MUZZLE | 100   | 200   | 300   | 400    |
| <b>VELOCITY</b>             | m/s | 795    | 717   | 644   | 575   | 509    |
| <b>ENERGY</b>               | J   | 3,539  | 2,879 | 2,320 | 1,849 | 1,453  |
| <b>DISTANCE</b>             | m   | 50     | 100   | 200   | 300   | 400    |
| <b>POINTS OF IMPACT</b>     | cm  | -0.3   | 0.0   | -14.2 | -52.1 | -119.9 |
| <b>POINTS OF IMPACT MRD</b> | cm  | 1.6    | 3.8   | -6.5  | -40.6 | -104.6 |

