

300 WIN. MAG. SPCE V340852 180 GRS



Semi-jacketed Soft Point Cutting Edge bullet. The cutting edge locks the jacket and lead core together, while also producing a clean entrance wound and distinct, easy to follow blood trails. Appropriate for light to medium game.



PROPERTIES

| | | |
|-------------------------------|--------------------|--|
| BULLET | TYPE | SPCE |
| | WEIGHT | grs 180 |
| | | g 11.70 |
| | SECTIONAL DENSITY | lb/in ² 0.271 |
| | MATERIAL OF JACKET | CuZn 10 |
| | NUMBER | 2935 |
| BALLISTIC COEFFICIENT | | G1 0.353 |
| | | G7 0.176 |
| MRD | | m 180 |
| CARTRIDGE | WEIGHT | g 32.2 |
| | LENGTH | mm 84.80 |
| CASINGS | | Factory Brass |
| POWER FACTOR ESTIMATED | kg·fps | 528.5 |
| +P AMMUNITION | | No |
| TEST BARREL LENGTH | mm | 600 |
| SUGGESTED USE | | Hunting |
| FEATURES | | Reliable Functioning, Rapid- Controlled Expansion, Accurate |
| PACKAGING | | |
| BOXES PER CASE | | 20 |
| WEIGHT PER CASE | kg | 14.2 |
| | lb | 31.5 |

BALLISTICS

| | | | | | | |
|-----------------------------|-----|--------|-------|-------|-------|-------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 895 | 806 | 722 | 643 | 569 |
| ENERGY | J | 4,686 | 3,799 | 3,046 | 2,416 | 1,893 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | -0.8 | 0.0 | -10.2 | -39.3 | -92.3 |
| POINTS OF IMPACT MRD | cm | 1.1 | 3.7 | -2.7 | -28.0 | -77.3 |

