

300 AAC BLACKOUT

FMJ V341292 147 GRS



Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.



PROPERTIES

| | | |
|-------------------------------|--|--------------------------|
| BULLET | TYPE | FMJ |
| WEIGHT | grs | 147 |
| | g | 9.55 |
| | SECTIONAL DENSITY | lb/in ² 0.221 |
| MATERIAL OF JACKET | CuZn 10 | |
| NUMBER | 2908 | |
| BALLISTIC COEFFICIENT | G1 | 0.407 |
| | G7 | 0.204 |
| MRD | m | 131 |
| CARTRIDGE | WEIGHT | g 17 |
| | LENGTH | mm 55.00 |
| CASINGS | N/A | |
| POWER FACTOR ESTIMATED | kg-fps | 305.3 |
| +P AMMUNITION | No | |
| TEST BARREL LENGTH | mm | 406 |
| SUGGESTED USE | Range, Match/Competition | |
| FEATURES | Reliable Functioning, Non-expanding, No Barrel Leading | |
| PACKAGING | | |
| BOXES PER CASE | 50 | |
| WEIGHT PER CASE | kg | 17.8 |
| | lb | 40.6 |

BALLISTICS

| | | | | | | |
|-----------------------------|-----|--------|-------|-------|-------|--------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 633 | 570 | 509 | 452 | 398 |
| ENERGY | J | 1,913 | 1,549 | 1,238 | 975 | 755 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | 0.9 | 0.0 | -25.4 | -88.8 | -200.6 |
| POINTS OF IMPACT MRD | cm | 2.5 | 3.2 | -18.9 | -79.1 | -187.6 |

