

300 AAC BLACKOUT

FMJ V341282 124 GRS



Full Metal Jacket bullet. Standard lead core with a metallic jacket. Best for training and target shooting applications.



PROPERTIES

| | | |
|-------------------------------|--|--------------------------|
| BULLET | TYPE | FMJ |
| WEIGHT | grs | 124 |
| | g | 8.00 |
| | SECTIONAL DENSITY | lb/in ² 0.187 |
| MATERIAL OF JACKET | CuZn 10 | |
| NUMBER | 2958 | |
| BALLISTIC COEFFICIENT | G1 | 0.379 |
| | G7 | 0.191 |
| MRD | m | 135 |
| CARTRIDGE | WEIGHT | g 15.5 |
| | LENGTH | mm 55.00 |
| CASINGS | N/A | |
| POWER FACTOR ESTIMATED | kg-fps | 268.5 |
| +P AMMUNITION | No | |
| TEST BARREL LENGTH | mm | 406 |
| SUGGESTED USE | Range, Match/Competition | |
| FEATURES | Reliable Functioning, Non-expanding, No Barrel Leading | |
| PACKAGING | | |
| BOXES PER CASE | 50 | |
| WEIGHT PER CASE | kg | 16.5 |
| | lb | 36.6 |

BALLISTICS

| | | | | | | |
|-----------------------------|-----|--------|-------|-------|-------|--------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 660 | 591 | 525 | 463 | 405 |
| ENERGY | J | 1,742 | 1,396 | 1,104 | 859 | 655 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | 0.6 | 0.0 | -23.2 | -82.2 | -187.3 |
| POINTS OF IMPACT MRD | cm | 2.4 | 3.4 | -16.4 | -71.9 | -173.5 |

