

30-06 SPRING. TXRG V342102 165 GRS



New generation lead free bullets Modern, highly efficient design incorporating a boat-tail base with a new, pointed tip for a flat trajectory and maximum retained energy. Blue plastic tip enhances expansion at all ranges while the solid copper construction maximizes weight retention.



PROPERTIES

| | | | |
|-------------------------------|--------------------|--------------------|-------|
| BULLET | TYPE | | TXRG |
| | WEIGHT | grs | 165 |
| | | g | 10.70 |
| | SECTIONAL DENSITY | lb/in ² | 0.248 |
| | MATERIAL OF JACKET | | - |
| | NUMBER | | 2971 |
| BALLISTIC COEFFICIENT | | G1 | 0.398 |
| | | G7 | 0.200 |
| MRD | | m | 173 |
| CARTRIDGE | WEIGHT | g | 27.1 |
| | LENGTH | mm | 84.80 |
| CASINGS | | | N/A |
| POWER FACTOR ESTIMATED | | kgf-fps | 459.5 |
| +P AMMUNITION | | | No |
| TEST BARREL LENGTH | | mm | 600 |
| SUGGESTED USE | | | N/A |
| FEATURES | | | N/A |
| PACKAGING | | | |
| BOXES PER CASE | | | 12 |
| WEIGHT PER CASE | | kg | 8.3 |
| | | lb | 18.3 |

BALLISTICS

| | | | | | | |
|-----------------------------|-----|--------|-------|-------|-------|-------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 849 | 772 | 700 | 631 | 567 |
| ENERGY | J | 3,856 | 3,192 | 2,620 | 2,132 | 1,718 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | -0.6 | 0.0 | -11.5 | -43.1 | -99.4 |
| POINTS OF IMPACT MRD | cm | 1.3 | 3.8 | -3.9 | -31.7 | -84.3 |

