


300 AAC BLACKOUT TXRG V341842 110 GRS



New generation lead free bullets Modern, highly efficient design incorporating a boat-tail base with a new, pointed tip for a flat trajectory and maximum retained energy. Blue plastic tip enhances expansion at all ranges while the solid copper construction maximizes weight retention.



PROPERTIES

BULLET	TYPE		TXRG
	WEIGHT	grs	110
		g	7.10
	SECTIONAL DENSITY	lb/in ²	0.166
	MATERIAL OF JACKET		-
	NUMBER		2973
BALLISTIC COEFFICIENT		G1	0.288
		G7	0.145
MRD		m	135
CARTRIDGE	WEIGHT	g	14.8
	LENGTH	mm	56.50
CASINGS			N/A
POWER FACTOR ESTIMATED		kgf-fps	243.7
+P AMMUNITION			No
TEST BARREL LENGTH		mm	410
SUGGESTED USE			N/A
FEATURES			N/A
PACKAGING			
BOXES PER CASE			50
WEIGHT PER CASE		kg	15.5
		lb	34.2

BALLISTICS

DISTANCE	m	MUZZLE	100	200	300	400
VELOCITY	m/s	675	584	499	420	348
ENERGY	J	1,617	1,209	883	625	430
DISTANCE	m	50	100	200	300	400
POINTS OF IMPACT	cm	0.6	0.0	-24.1	-88.1	-208.5
POINTS OF IMPACT MRD	cm	2.3	3.5	-17.2	-77.7	-194.7

