

7 × 64 TXRG V342142 150 GRS



New generation lead free bullets Modern, highly efficient design incorporating a boat-tail base with a new, pointed tip for a flat trajectory and maximum retained energy. Blue plastic tip enhances expansion at all ranges while the solid copper construction maximizes weight retention.



PROPERTIES

| | | | |
|-------------------------------|--------------------|--------------------|-------|
| BULLET | TYPE | | TXRG |
| | WEIGHT | grs | 150 |
| | | g | 9.70 |
| | SECTIONAL DENSITY | lb/in ² | N/A |
| | MATERIAL OF JACKET | | - |
| | NUMBER | | 2969 |
| BALLISTIC COEFFICIENT | | G1 | 0.449 |
| | | G7 | 0.226 |
| MRD | | m | 175 |
| CARTRIDGE | WEIGHT | g | 26 |
| | LENGTH | mm | 84.00 |
| CASINGS | | | N/A |
| POWER FACTOR ESTIMATED | | kgf-fps | 420.3 |
| +P AMMUNITION | | | No |
| TEST BARREL LENGTH | | mm | 600 |
| SUGGESTED USE | | | N/A |
| FEATURES | | | N/A |
| PACKAGING | | | |
| BOXES PER CASE | | | 12 |
| WEIGHT PER CASE | | kg | 7.7 |
| | | lb | 17 |

BALLISTICS

| | | | | | | |
|-----------------------------|-----|--------|-------|-------|-------|-------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 854 | 786 | 721 | 659 | 600 |
| ENERGY | J | 3,537 | 2,995 | 2,519 | 2,105 | 1,747 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | -0.7 | 0.0 | -10.9 | -40.8 | -93.3 |
| POINTS OF IMPACT MRD | cm | 1.2 | 3.8 | -3.4 | -29.5 | -78.2 |

