

308 WIN.

XRG V342532 180 GRS



S&B's original solid copper hunting bullet designed for deep penetration and high weight retention on the toughest game animals.



PROPERTIES

| | | |
|-------------------------------|---|--------------------------|
| BULLET | TYPE | XRG |
| | WEIGHT | grs 180 |
| | | g 11.70 |
| | SECTIONAL DENSITY | lb/in ² 0.271 |
| | MATERIAL OF JACKET | - |
| | NUMBER | 2970 |
| BALLISTIC COEFFICIENT | G1 | 0.287 |
| | G7 | 0.144 |
| MRD | m | 158 |
| CARTRIDGE | WEIGHT | g 25.9 |
| | LENGTH | mm 71.10 |
| CASINGS | Factory Brass | |
| POWER FACTOR ESTIMATED | kgr-fps | 469.4 |
| +P AMMUNITION | No | |
| TEST BARREL LENGTH | mm | 600 |
| SUGGESTED USE | Hunting | |
| FEATURES | 100% Solid Copper, Reliable Functioning, Deep Penetration, Accurate | |
| PACKAGING | | |
| BOXES PER CASE | 10 | |
| WEIGHT PER CASE | kg | 6.3 |
| | lb | 14 |

BALLISTICS

| | | | | | | |
|-----------------------------|-----|--------|-------|-------|-------|--------|
| DISTANCE | m | MUZZLE | 100 | 200 | 300 | 400 |
| VELOCITY | m/s | 795 | 694 | 600 | 513 | 433 |
| ENERGY | J | 3,697 | 2,814 | 2,106 | 1,542 | 1,095 |
| DISTANCE | m | 50 | 100 | 200 | 300 | 400 |
| POINTS OF IMPACT | cm | -0.3 | 0.0 | -15.6 | -58.6 | -139.3 |
| POINTS OF IMPACT MRD | cm | 1.6 | 3.8 | -7.9 | -47.1 | -123.9 |

